

Storage & Backups (out-of-date)

Create `zpool10` Storage Pool

The host's `rpool` (default ZFS pool used by Proxmox) can be used for templates and whatnot but I want a big pool for storing all my data. So I created a ZFS RAIDZ2 pool using 6x 10TB HDDs.

This is the command I used to build my ZFS pool.

```
# zpool create -o ashift=12 -o failmode=continue -O compression=lz4 -O xattr=sa -O atime=off \  
-O encryption=aes-256-gcm -O keyformat=passphrase \  
-m /storage/zpool10 zpool10 raidz2 \  
/dev/disk/by-id/ata-WDC_WD100EMAZ-00WJTA0_JEKH3DVZ \  
/dev/disk/by-id/ata-WDC_WD100EMAZ-00WJTA0_2YK148SD \  
/dev/disk/by-id/ata-WDC_WD100EMAZ-00WJTA0_JEKH8RWZ \  
/dev/disk/by-id/ata-WDC_WD100EMAZ-00WJTA0_JEK6ESAN \  
/dev/disk/by-id/ata-WDC_WD100EMAZ-00WJTA0_JEK53ZHN \  
/dev/disk/by-id/ata-WDC_WD100EMAZ-00WJTA0_2YK0HL0D
```

- `ashift=12` to use 4k blocks
- `failmode=continue` to let us keep reading if a drive goes bad
- `compression=lz4` save save space and increase speed
- `xattr=sa` be more efficient for linux attributes
- `atime=off` don't waste time tracking access times for files
- `encryption=aes-256-gcm` use fast/secure encryption algorithm
- `keyformat=passphrase` unlock with a passphrase

Setup ZFS Scrub (Data Integrity)

Automate [ZFS scrubbing](#) so the data integrity on disks is actively monitored, repaired if necessary, and I'm alerted if there is a problem with my disks.

Create systemd Service/Timer ([source](#))

Create a simple systemd service template for scrubbing ZFS pools.

```
# /etc/systemd/system/zpool-scrub@.service
+ [Unit]
+ Description=Scrub ZFS Pool
+ Requires=zfs.target
+ After=zfs.target
+
+ [Service]
+ Type=oneshot
+ ExecStartPre=-/usr/sbin/zpool scrub -s %I
+ ExecStart=/usr/sbin/zpool scrub %I
```

Then create a systemd timer template for periodically running that service. I am running the scrub weekly, but semi-monthly or monthly would almost certainly be ok too.

```
# /etc/systemd/system/zpool-scrub@.timer
+ [Unit]
+ Description=Scrub ZFS pool weekly
+
+ [Timer]
+ OnCalendar=weekly
+ Persistent=true
+
+ [Install]
+ WantedBy=timers.target
```

Enable ZFS Scrub

```
systemctl daemon-reload
systemctl enable --now zpool-scrub@rpool.timer
systemctl enable --now zpool-scrub@zpool10.timer
```

Setup Storage Layout

I wanted to logically device my storage pool up into datasets based on their intended usage. This allows me to tweak their parameters if needed and have different snapshot/backup policies.

- `zpool10/backups` place to store disk and time machine backups
- `zpool10/downloads` storage for downloads

- `zpool10/downloads/incomplete` landing zone for incomplete downloads (`recordsize=1M` for bittorrent)
- `zpool10/media` storage for audio/tv/movies
- `zpool10/proxmox` additional storage for proxmox
- `zpool10/proxmox/backups` backup for proxmox instances (in subdirectories by hostname)
- `zpool10/services` storage for services (possibly databases, so use `recordsize=16k`)

```
zfs create zpool10/backups
zfs create zpool10/downloads
zfs create -o recordsize=1M zpool10/downloads/incomplete
zfs create zpool10/media
zfs create zpool10/proxmox
zfs create zpool10/proxmox/backups
zfs create -o recordsize=16K zpool10/services
```

Setup Sanoid/Syncoid (Data Backup)

Run [Sanoid](#) for automating snapshots and Syncoid for remote backups. Unfortunately this isn't available in repositories so you have to build it yourself. However the author makes it fairly simple.

Install ([source](#))

```
apt-get install debhelper libcapture-tiny-perl libconfig-inifiles-perl pv lzop mbuffer
sudo git clone https://github.com/jimsalterjrs/sanoid.git
cd sanoid
ln -s packages/debian .
dpkg-buildpackage -uc -us
apt install ../sanoid_*_all.deb
```

Configure Sanoid

I want to take hourly snapshots of both of my ZFS pools because sometimes I am not as careful or thoughtful as I should be about what I am doing at any given moment. But I don't want to snapshot `zpool/backups` because it is a backup destination that will likely already have snapshots (`rpool` snapshots are stored there for example) and I also don't want to snapshot `zpool/downloads` because there is nothing important under there and it is likely to change frequently.

```
# /etc/sanoid/sanoid.conf
+ [template_proxmox]
+     frequently = 0
```

```
+ hourly = 24
+ daily = 7
+ weekly = 4
+ monthly = 1
+ yearly = 0
+ autosnap = yes
+ autoprune = yes
+
+ [rpool]
+ use_template = template_proxmox
+ process_children_only = yes
+ recursive = yes
+
+ [rpool/ROOT]
+ use_template = rpool
+ process_children_only = yes
+ recursive = yes
+
+ [rpool/data]
+ use_template = template_proxmox
+ weekly = 1
+ monthly = 1
+ process_children_only = yes
+ recursive = yes
```

Maybe this is a sin, but I'd like my snapshots to be in local time so I don't have to do the (admittedly simple) conversion in my head.

```
# /usr/lib/systemd/system/sanoid.service
[Service]
- Environment=TZ=UTC
+ Environment=TZ=EST
```

Eanble Sanoid

```
systemctl daemon-reload
systemctl enable --now sanoid.service
```

Configure Syncoid

Backup `rpool` to `zpool10/proxmox/backups/blackbox`

Right now `rpool` is just running on a single non-redundant 512GB SSD disk. Even though it is only used for Proxmox (config, templates, ISOs) this isn't great practice and I'll work on this in the future. But in the meantime I am backing up everything on a daily timer to my main ZFS pool so I could recover very quickly if the SSD dies.

```
# /etc/systemd/system/rpool-backup.timer
+ [Unit]
+ Description=Backup rpool daily
+
+ [Timer]
+ OnCalendar=daily
+ Persistent=true
+
+ [Install]
+ WantedBy=timers.target
```

```
# /etc/systemd/system/rpool-backup.service
+ [Unit]
+ Description=Use syncoid to backup rpool to zpool10/proxmox/backups/blackbox
+ Requires=zfs.target
+ After=zfs.target
+
+ [Service]
+ Type=oneshot
+ ExecStart=/usr/sbin/syncoid --force-delete --recursive rpool zpool10/proxmox/backups/blackbox/rpool
```

Backup `zpool10/services` offsite

All my docker containers store their configuration and data under the `zpool10/services` dataset. It is imperative this is backed up offsite so if anything catastrophic ever happens I don't lose anything important and can get back up and running as quickly as I can download my backup.

```
# /etc/systemd/system/zpool10-services-backup.timer
+ [Unit]
+ Description=Backup zpool10/services daily
+
+ [Timer]
+ OnCalendar=daily
+ Persistent=true
```

```
+  
+ [Install]  
+ WantedBy=timers.target
```

```
# /etc/systemd/system/zpool10-services-backup.service  
+ [Unit]  
+ Description=Use syncoid to backup zpool10/services to backedup.swigg.net:bpool/zpool10/services  
+ Requires=zfs.target  
+ After=zfs.target  
+  
+ [Service]  
+ Type=oneshot  
+ ExecStart=/usr/sbin/syncoid --force-delete --recursive zpool10/services  
root@backedup.swigg.net:bpool/zpool10/services
```

Enable Syncoid

```
systemctl daemon-reload  
systemctl enable --now rpool-backup.timer
```

Setup Restic to Backblaze B2 (Data Backup)

Read more about setting up Restic at <https://fedoramagazine.org/automate-backups-with-restic-and-systemd/>

Setup Restic Backup

Create the `.service` and `.timer` for the backup service so that it runs everyday.

```
# /etc/systemd/system/restic-backup.service  
+ [Unit]  
+ Description=Restic backup service  
+  
+ [Service]  
+ Type=oneshot  
+ ExecStart=restic backup --verbose --tag systemd.timer $BACKUP_EXCLUDES $BACKUP_INCLUDES  
$BACKUP_PATHS
```

```
+ ExecStartPost=restic forget --verbose --tag systemd.timer --group-by "paths,tags" --keep-daily
$RETENTION_DAYS --keep-weekly $RETENTION_WEEKS --keep-monthly $RETENTION_MONTHS --keep-yearly
$RETENTION_YEARS
+ EnvironmentFile=/etc/systemd/system/restic-backup.service.d/restic-backup.conf
```

```
# /etc/systemd/system/restic-backup.timer
+ [Unit]
+ Description=Backup with restic daily
+
+ [Timer]
+ OnCalendar=daily
+ Persistent=true
+
+ [Install]
+ WantedBy=timers.target
```

```
# /etc/systemd/system/restic-backup.service.d/restic-backup.conf
+ BACKUP_PATHS="/storage/zpool10"
+ BACKUP_EXCLUDES="--exclude-file /etc/systemd/system/restic-backup.service.d/restic-excludes.txt --exclude-
if-present .exclude_from_backup"
+ BACKUP_INCLUDES="--files-from /etc/systemd/system/restic-backup.service.d/restic-includes.txt"
+ RETENTION_DAYS=7
+ RETENTION_WEEKS=4
+ RETENTION_MONTHS=6
+ RETENTION_YEARS=3
+ B2_ACCOUNT_ID=xxx
+ B2_ACCOUNT_KEY=xxx
+ RESTIC_REPOSITORY=b2:swigg-backup-blackbox:storage/zpool10
+ RESTIC_PASSWORD=xxx
```

Setup Restic Prune

The backup command above forgets about files when they expire, but to actually delete them once they aren't referenced anymore you need to prune them. The following creates a `.service` and `.timer` for a prune job to be run every month.

```
# /etc/systemd/system/restic-prune.service
+ [Unit]
+ Description=Restic backup service (data pruning)
+
```

```
+ [Service]
+ Type=oneshot
+ ExecStart=restic prune
+ EnvironmentFile=/etc/systemd/system/restic-backup.service.d/restic-backup.conf
```

```
# /etc/systemd/system/restic-prune.timer
+ [Unit]
+ Description=Prune data from the restic repository monthly
+
+ [Timer]
+ OnCalendar=monthly
+ Persistent=true
+
+ [Install]
+ WantedBy=timers.target
```

Revision #26

Created 4 January 2020 05:24:53 by Dustin Sweigart

Updated 26 April 2021 12:04:42 by dustin@swigg.net