

outpost

Debian box for hosting e-mail and LDAP services.

- [Physical Hardware](#)
- [Base Install](#)

Physical Hardware

Basic Components

Proectli Vault

Compute

Processor	Intel Celeron Bay Trail-D J1800 <ul style="list-style-type: none">• 64-bit• 2-cores / 2-threads• 2.41GHz base, 2.58GHz burst• 2MB L2 Cache
GPU	HD Graphics for Intel Atom Processor Z3700 Series <ul style="list-style-type: none">• Intel Quick Sync Video• 688 MHz base, 792MHz Max Dynamic

Motherboard

Memory	1x SO-DIMM DDR3L-1333, 1.35v, Max 8GB
Storage	1x mSATA SSD, Max 1 TB
Display	1x VGA
Networking	2x Intel Gigabit 82583V Ethernet NIC ports
USB	1x USB 2.0, 1x USB 3.0
COM Port	1x RJ45

Memory

Manufacturer	Timetec Hynix IC
--------------	------------------

Type	DDR3
Capacity	8GB
Speed	1600MHz PCL-12800
Specifications	Non ECC Unbuffered 1.35V CL11 2Rx8 Dual Rank 204 Pin SODIMM

Storage

Manufacturer	Dogfish
Type	SSD
Capacity	64GB
Interface	mSATA
Speed	SATA3 6.0Gb/s

Base Install

Operation System

Proxmox Virtual Environment 6.x