outpost

Debian box for hosting e-mail and LDAP services.

- Physical Hardware
- Base Install

Physical Hardware

Basic Components

Proectli Vault

Compute

Processor	Intel Celeron Bay Trail-D J1800 • 64-bit • 2-cores / 2-threads • 2.41GHz base, 2.58GHz burst • 2MB L2 Cache
GPU	HD Graphics for Intel Atom Processor Z3700 Series • Intel Quick Sync Video • 688 MHz base, 792MHz Max Dynamic

Motherboard

Memory	1x SO-DIMM DDR3L-1333, 1.35v, Max 8GB
Storage	1x mSATA SSD, Max 1 TB
Display	1x VGA
Networking	2x Intel Gigabit 82583V Ethernet NIC ports
USB	1x USB 2.0, 1x USB 3.0
COM Port	1x RJ45

Memory

Manufacturer	Timetec Hynix IC

Type	DDR3
Capacity	8GB
Speed	1600MHz PCL-12800
Specifications	Non ECC Unbuffered 1.35V CL11 2Rx8 Dual Rank 204 Pin SODIMM

Storage

Manufacturer	Dogfish
Type	SSD
Capacity	64GB
Interface	mSATA
Speed	SATA3 6.0Gb/s

Base Install

Operation System

Proxmox Virtual Environment 6.x